

# PRODUCT AK-75

## 1. GENERAL DESCRIPTION

- A variety of two-component Polyurethane Coating can be as a hardener

## 2. FEATURES

- Fast drying
- Compatibility with polyol, solvent
- Solubility
- Cold-proof

## 3. APPLICATIONS

- Wood and metal finishes
- Fabric and paper coatings
- Coatings on plastics and rubber
- Adhesive for papers, synthetic leathers and film
- Ink

## 4. SPECIFICATIONS

Property	Unit	Value
Non Volatile Content	-	74.0 - 76.0
Viscosity (25 °C)	Gardner	V - Y
NCO CONTENT	%	12.5 - 13.5
Free Monomer	%	0.5 Max

## 5. GUIDELINES for USE

- Be sure to read the MSDS, Technical data and Warnings before using please.
- Likely to result in injury due to solvent vapors compressed, please be careful.
- Has the possibility change the viscosity of the product when stored for a long time.

## 6. STORAGE GUIDE

- After use, the remaining sealed to prevent moisture from entering the indoor storage, please.

## 7. REFERENCES

- When used alone may be not cure.
- There is a possibility to be a compatibility problem when you use with another hardener.
- Mixed with the water-soluble resin used is the cause of the defects.

This document is prepared by SRC INTERNATIONAL authorized person. For more information please visit [www.srcinterlog.com](http://www.srcinterlog.com)

ÇINARLI, 1563 Sk. No:2, İNCİ TOWER D:65; P:35170, Konak, İZMİR - TURKEY  
Tel: +90 530 592 9719 [info@srcinterlog.com](mailto:info@srcinterlog.com)

