

## PRODUCT ATH-5060EA

### 1. GENERAL DESCRIPTION

- A variety of two-component Polyurethane Coating can be as a hardener

### 2. Features

- Weather resistance (Low yellowing)
- Fast dry

### 3. APPLICATIONS

- Wood, Metal
- Plastic, Synthetic leather
- Adhesives

### 4. SPECIFICATIONS OF RESIN

Property	Unit	Value
Non Volatile Content	-	59.0 – 61.0
Viscosity (25°C)	cps	500 - 2500
NCO CONTENT	%	9.0 – 11.0
Color	APHA	60 Max
Free Monomer	%	1.0 Max

### 5. USE OF RESIN

- Be sure to read the MSDS, Technical data and Warnings before using please.
- Likely to result in injury due to solvent vapors compressed, please be careful.
- Has the possibility change the viscosity of the product when stored for a long time.

### 6. STORAGE AND REMAINING GUIDE & SAFETY

- After use, the remaining sealed to prevent moisture from entering the indoor storage, please.

### 7. REFERENCES

- When used alone may be not cure.
- There is a possibility to be a compatibility problem when you use with another hardener.
- Mixed with the water-soluble resin used is the cause of the defects.

This document is prepared by SRC INTERNATIONAL authorized person. For more information please visit [www.srcinterlog.com](http://www.srcinterlog.com)

ÇINARLI, 1563 Sk. No:2, İNCİ TOWER D:65; P:35170, Konak, İZMİR - TURKEY  
Tel: +90 530 592 9719 [info@srcinterlog.com](mailto:info@srcinterlog.com)